

Standofleet. VOC-compliant products.



The Art of Refinishing.

Standofleet from Standox is the complete system for commercial vehicle refinishing that complies with the stringent EU VOC limits.



Standofleet. Good for our environment, ideal for your business.

The modular structure of the Standofleet refinishing system makes it extremely adaptable to use. No matter what the job at hand – a truck chassis, a dumper body, an articulated trailer or a liveried bus repair on steel, aluminium or plastic – Standofleet is always the right choice.

The right combination of concentrated mixing tints and binders allows the refinisher to create different grades of topcoat. Yet despite the flexibility of the Standofleet system, it is made up of only a few products. Just 26 tints cover the fully CV solid color offer, with the benefits of an adaptable system and low stocking.

Nearly all Standofleet products are based on state-of-the-art high-solids technology. The high solid content not only guarantees a high coverage and good opacity but also ensures that all VOC requirements are met.

This means that Standofleet excels not only in terms of environmental compatibility but also in terms of cost effective and profitable refinishing. This is your “green ticket” to becoming even more competitive.



The Standofleet VOC range.

This Standofleet range includes all products that meet the stringent EU VOC (volatile organic compounds) limits. The VOC figures quoted are ready for use.

Stopper

max. permissible VOC limit 250 g/l
Standox PE Soft Stopper

Wash Primer

max. permissible VOC limit 780 g/l
Standofleet Wash Primer
Standofleet 1K Primer
Standofleet Reaction Primer
Standofleet 1K Welding Primer

Primer Filler, Wet-on-wet Filler, Sanding Filler

max. permissible VOC limit 540 g/l
Standofleet 2K VOC Sanding Filler
Standofleet 2K VOC Wet-on-wet Filler
Standofleet Epoxy Surfacer 5:1
Standofleet 2K Primer Surfacer
Standofleet 2K Non Sanding Filler
Standofleet 2K VOC Universal Filler
Standofleet 2K VOC High Build Primer
Standofleet 2K Sealer

Solid-color Topcoat

max. permissible VOC limit 420 g/l
Standofleet 2K HS Topcoat
Standofleet 2K HS High Build Topcoat

Clearcoat

max. permissible VOC limit 420 g/l
Standofleet 2K VOC Clear
Standofleet 2K HS Clear





Standex GmbH · Postfach · D-42271 Wuppertal · Germany